

### HARDWARE FEATURES

Interface	1 × 10/100/1000 Mbps LAN/WAN Port 3 × 10/100/1000 Mbps LAN Ports 1 × Micro SIM Card Slot
Button	WPS/Reset Button, WiFi On/Off Button, Power On/Off Button
External Power Supply	Power Adapter: : Input Power 100-240v~50/60 Hz 0.6A Output parameter 12VDC 1.5A
Dimensions ( W x D x H )	202 × 141 × 33.6 mm (7.95 × 5.55 × 1.32 in)
Antenna	2 × Detachable 4G LTE Antennas

### WIRELESS FEATURES

Wireless Standards	IEEE 802.11a/n/ac 5 GHz, IEEE 802.11b/g/n 2.4 GHz
Frequency	2.4 GHz and 5 GHz
Signal Rate	300 Mbps at 2.4 GHz, 867 Mbps at 5 GHz
Reception Sensitivity	5 GHz: 11a 54M: -77 dBm 11ac HT20: -73 dBm 11ac HT40: -68 dBm 11ac HT80 : -64 dBm 11n HT20: -77 dBm 11n HT40: -73 dBm 2.4 GHz: 11g 54M: -74 dBm 11n HT20: -72 dBm 11n HT40: -69 dBm

## WIRELESS FEATURES

Transmit Power	< 20 dBm (2.4 GHz), < 23 dBm (5 GHz)
Wireless Functions	Enable/Disable Wireless Radio, Wireless Schedule, WMM, Wireless Statistics
WAN Failover	Yes
Wireless Security	64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK encryptions
Network Type	4G: FDD-LTE: B1/B3/B5/B7/B8/B20/B28 (2100/1800/850/2600/900/800/700 MHz) TDD-LTE: B38/B40/B41 (2600/2300/2555-2655 MHz) 3G: DC-HSPA+/HSPA/UMTS: B1/B5/B8 (2100/850/900 MHz)  Carrier Aggregation: B1+B3/B5/B7/B8/B20 B3+B1/B3/B5/B7/B8/B20/B28/B38/B40 B5+B1/B3/B5/B7/B40 B7+B1/B3/B5/B7/B8/B20/B28 B8+B1/B3/B7 B20+B1/B3/B7 B28+B3/B7/B40 B38+B38 B40+B40 B41+B41

## SOFTWARE FEATURES

Quality of Service	Bandwidth Control
Security	DoS, IPv4 SPI Firewall, IPv6 Firewal, IP and MAC Address Binding, Access Control
WAN Type	Dynamic IP/Static IP/PPPoE/PPTP(Dual Access)/L2TP(Dual Access)
Management	TP-Link Cloud, Local Management, Remote Management
DHCP	Server, DHCP Client List, Address Reservation
Port Forwarding	ALG, Virtual Server, Port Triggering, UPnP, DMZ

## SOFTWARE FEATURES

Dynamic DNS	TP-Link, DynDns, NO-IP
VPN	PPTP VPN, OpenVPN
Access Control	Parental Control, Local Management Control
Firewall Security	DoS, SPI Firewall, IP Address Filter/Domain Filter, IP and MAC Address Binding
Protocols	IPv4, IPv6
Guest Network	2.4 GHz Guest Network x 1, 5 GHz Guest Network x 1

## OTHERS

Certification	CE, RoHS
Package Contents	4G+ Cat6 AC1200 Wireless Dual Band Gigabit Router Archer MR600 Power Adapter RJ45 Ethernet Cable Quick Installation Guide
Environment	Operating Temperature: 0°C~40°C (32°F ~104°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing

[For additional version information, please go to the support page.](#)

\*Maximum wireless signal rates are the physical rates derived from IEEE Standard 802.11 specifications. Actual wireless data throughput and wireless coverage, and quantity of connected devices are not guaranteed and will vary as a result of network conditions, client limitations, and environmental factors, including building materials, obstacles, volume and density of traffic, and client location.

**Sign up for news & offers** ⓘ

**Follow Us**